



1626 Bridgewater Road • Bensalem, PA 19020 • 800-331-1373 • fax 215-245-8554

www.prestotape.com

105 Strapping Tape

Technical Data

Product Description:

This product is a general purpose high strength tape used for palletizing, bundling, color-coding, and unitizing. It is constructed of a tensilized MOPP film with a water-based acrylic adhesive system. As a standard product it is available in clear, white and black and in widths from 9mm to 48mm.

Product Properties / Characteristics:

	Nominal Results
Adhesion to Steel: PSTC 1 oz./in.	30.0 to 32.0
Tack Level:	High
Tensile Strength: PSTC 31 lb./sq. in.	97
Elongation (%): PSTC 31	35 %
Thickness: PSTC 33	2.8 mils (nominal)

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

Limitations of Warranty: Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape’s option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.