



1626 Bridgewater Road • Bensalem, PA 19020 • 800-331-1373 • fax 215-245-8554

[www.prestotape.com](http://www.prestotape.com)

# 15L10 Low Tack Protection Film

## Technical Data

### Product Description:

This product is a temporary protective mask designed for use on matte and semi-gloss surfaces. It provides excellent protection for painted or treated aluminum, plastics, and similar surfaces. The 15L10 product is available in clear, blue and white LDPE film with an acrylic adhesive systems that allows clean removal with minimal adhesion buildup.

### Product Properties / Characteristics:

	<u>Nominal Results</u>
<b>Adhesion to Steel:</b> PSTC 1 oz./in.	<b>0.5 to 1.5</b>
<b>Tack Level:</b>	<b>Low</b>
<b>Tensile Strength:</b> PSTC 31 lb./sq. in.	<b>7</b>
<b>Elongation (%):</b> PSTC 31	<b>325 MD</b>
<b>Thickness:</b> PSTC 33	<b>1.5 mils (nominal)</b>

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

**Limitations of Warranty:** Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.