



1626 Bridgewater Road • Bensalem, PA 19020 • 800-331-1373 • fax 215-245-8554

[www.prestotape.com](http://www.prestotape.com)

# 160 ECO Carton Seal Tape

## Technical Data

### Product Description:

The 160 ECO carton sealing tape is a product that uses our Eco Zone Coat Technology (Patent # 5922402). This tape is coated on the edges, leaving the center of the tape adhesive free. This construction provides a viable product for most applications with an environmental savings. It is made of a BOPP film with an aggressive water-based acrylic adhesive system. The 160 ECO tape is Made in the U. S. A.

### Product Properties / Characteristics:

	Nominal Results
<b>Adhesion to Steel:</b> PSTC 1 oz./in.	19
<b>Tack Level:</b>	High
<b>Tensile Strength:</b> PSTC 31 lb./sq. in.	19
<b>Elongation (%):</b> PSTC 31	140 %
<b>Thickness:</b> PSTC 33	1.6 mils

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

**Limitations of Warranty:** Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape’s option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.

