



1626 Bridgewater Road • Bensalem, PA 19020 • 800-331-1373 • fax 215-245-8554

[www.prestotape.com](http://www.prestotape.com)

# 20C40 Medium Tack Co-Extruded Protection Film

## Technical Data

### Product Description:

This is a temporary surface protection product with a medium tack adhesive for the protection of semi-smooth and textured surfaces. It is excellent protection for polished stainless steel and similar surfaces. This product provides excellent protection from abrasion during forming and in storage. It is constructed of a clear co-extruded multi-polymer polyethylene film with a water-based acrylic adhesive.

### Product Properties / Characteristics:

	Nominal Results
<b>Adhesion to Steel:</b> PSTC 1 oz./in.	2.0 – 4.0
<b>Tack Level:</b>	Medium
<b>Tensile Strength:</b> PSTC 31 lb./sq. in.	9
<b>Elongation (%):</b> PSTC 31	600 MD
<b>Thickness:</b> PSTC 33	2 mils (nominal)

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

**Limitations of Warranty:** Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape’s option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.