



1626 Bridgewater Road • Bensalem, PA 19020 • 800-331-1373 • fax 215-245-8554

www.prestotape.com

30A80 Heavy Duty Carpet Protection Film

Technical Data

Product Description:

This is a temporary masking product designed to protect synthetic carpets from tracked in dirt, paint spills, dust, construction debris and damage. The polyethylene film is a special blend which is resistant to tears and punctures from sharp items such as tools or high heels. The acrylic adhesive system allows for clean removal. The maximum protection time is 45 days. This product should not be used in high humidity conditions or in outdoor applications.

Product Properties / Characteristics:

	Nominal Results
Tack Level:	High
Tensile Strength: PSTC 31 lb./sq. in.	11
Elongation (%): PSTC 31	630 MD
Thickness: PSTC 33	3 mils (nominal)

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

Limitations of Warranty: Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape’s option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.