



1626 Bridgewater Road • Bensalem, PA 19020 • 800-331-1373 • fax 215-245-8554

www.prestotape.com

702 and 702ET All Weather Tape

Technical Data

Product Description:

This product is a heavy duty clear tape designed for general purpose indoor and outdoor use. The film, which contains a UVI additive, along with the water-based acrylic adhesive system combine to make the 702 tape ideal for greenhouse patchwork, seaming, splicing and heavy bundling. The 702 tape is available with a serrated edge that makes it into an easy tear product.

Product Properties / Characteristics:

	Nominal Results
Adhesion to Steel: PSTC 1 oz./in.	30.0 to 40.0
Tack Level:	Very High
Tensile Strength: PSTC 31 lb./sq. in.	31
Elongation (%): PSTC 31	325 MD
Thickness: PSTC 33	5 mils (nominal)

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

Limitations of Warranty: Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape’s option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.